

## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A method comprising:  
determining an ambient light level for an operating environment of a display device having an adjustable backlight to provide variable brightness; ~~and~~  
modifying ~~color~~ luminance values corresponding to one or more portions of an image to be displayed on the display device based on the ambient light level; and  
modifying the backlight intensity based on the modified luminance values  
wherein modification to the backlight intensity approximately offsets the modification to the luminance values.

2-3. (Canceled)

4. (Original) The method of claim 1 wherein determining the ambient light level comprises receiving a signal from an ambient light sensor indicating the ambient light level.

5. (Original) The method of claim 1 wherein determining the ambient light level comprises receiving a user input.

6. (Currently Amended) The method of claim 1 wherein modifying the luminance values ~~color brightness~~ comprises modifying a color look-up table.

7. (Currently Amended) The method of claim 1 ~~2~~ wherein modifying the backlight intensity comprises modifying a pulse width modulation signal that controls backlight illumination.

8. (Currently Amended) The method of claim 1 ~~2~~ wherein modifying the backlight intensity comprises:

determining a hardware register value corresponding to a baseline backlight intensity value;

applying a software generated value to the register value to generate a modified backlight intensity value; and

using the modified backlight intensity value to cause the backlight intensity to be modified.

9. (Original) The method of claim 8 wherein the baseline backlight intensity value is determined based on a user provided input.

10. (Original) The method of claim 8 wherein the baseline backlight intensity value is determined based on a power state of the display device.

11. (Original) The method of claim 8 wherein the hardware register value is stored in a register within a Peripheral Component Interconnect configuration space.

12. (Currently Amended) A method comprising:  
determining an ambient light level for a display device having an adjustable backlight to provide variable backlight intensity;  
modifying the backlight intensity based on the ambient light level; and  
modifying a ~~color~~ luminance values corresponding to one or more portions of an image to be displayed on the display device based on the modified intensity of the adjustable backlight;  
wherein modification to the luminance values approximately offsets the modification to the backlight intensity.

13. (Canceled)

14. (Original) The method of claim 12 wherein determining the ambient light level comprises receiving a signal from an ambient light sensor indicating an ambient light level.

15. (Original) The method of claim 12 wherein determining the ambient light level comprises receiving a user input.

16. (Currently Amended) The method of claim 12 wherein modifying the luminance values ~~color brightness~~ comprises modifying a pixel color using a graphics controller look-up table prior to passing the pixel to the display device.

17. (Original) The method of claim 12 wherein modifying the backlight intensity comprises modifying a pulse width modulation signal that controls backlight illumination.

18. (Previously Presented) The method of claim 12 wherein modifying the backlight intensity comprises:

determining a hardware register value corresponding to a baseline backlight intensity value;

applying a software generated value to the register value to generate a modified backlight intensity value; and

using the modified backlight intensity value to cause the backlight intensity to be modified.

19. (Original) The method of claim 18 wherein the baseline backlight intensity value is determined based on a user provided input.

20. (Original) The method of claim 18 wherein the baseline backlight intensity value is determined based on a power state of the display device.

21. (Original) The method of claim 18 wherein the hardware register value is stored in a register within a Peripheral Component Interconnect configuration space.

22. (Currently Amended) An apparatus comprising:  
an ambient light sensor to generate signals indicating a sensed ambient light level;  
a display device having an adjustable backlight source; and  
a graphics control device coupled with the ambient light sensor on the display device, the graphics control device to modify luminance values corresponding to one or more portions of an image and backlight intensity based on the sensed ambient light level;

wherein the graphics control device modifies backlight intensity based on the sensed ambient light level and modifies the luminance values corresponding to one or more portions of an image to be displayed on the display device based on the modified backlight intensity.

23-24. (Canceled)

25. (Original) The apparatus of claim 22 wherein the display device comprises a flat-panel liquid crystal display.

26. (Original) The apparatus of claim 22 wherein the display device comprises a plasma display device.

27. (Original) The apparatus of claim 22 wherein the graphics control device comprises:

a backlight control circuit coupled with the adjustable backlight source to control the intensity of backlight provided by the adjustable backlight source; and

a display control circuit coupled with the ambient light sensor and the backlight control circuit to apply an adjustment to a baseline backlight including at least the sensed ambient light level to generate a modified backlight intensity signal;

wherein the backlight control circuit causes the adjustable backlight source to provide a backlight intensity corresponding to the modified backlight intensity value.

28. (Original) The apparatus of claim 27 wherein the backlight control circuit provides a pulse width modulated signal to the adjustable backlight source to control the intensity of the backlight provided by the adjustable backlight source.

29. (Original) The apparatus of claim 27 wherein the baseline backlight intensity is retrieved from a register coupled with the backlight controller.

30. (Original) The apparatus of claim 27 wherein the adjustment to the baseline backlight intensity further comprises user-specified adjustment parameters.

31. (Original) The apparatus of claim 30 wherein the user-specified adjustment parameters comprise a range of desired backlight adjustments.

32. (Currently Amended) An article comprising a computer-readable storage medium having stored thereon instructions that, when executed, cause one or more processing devices to:

determine an ambient light level for a display device having an adjustable backlight to provide variable backlight intensity; ~~and~~

modify ~~a color~~ luminance values corresponding to one or more portions of an image to be displayed on the display device based on the ambient light level; and

modify the backlight intensity based on the modified luminance values  
wherein modification to the backlight intensity approximately offsets the modification to the luminance values.

33-34. (Canceled)

35. (Original) The article of claim 32 wherein the instructions that cause the one or more processing devices to determine the ambient light level comprise instructions that, when executed, cause the one or more processing devices to receive a signal from an ambient light sensor indicating the ambient light level.

36. (Original) The article of claim 32 wherein the instructions that cause the one or more processing devices to determine the ambient light level comprise instructions that, when executed, cause the one or more processing devices to receive a user input.

37. (Currently Amended) The article of claim 32 wherein the instructions that cause the one or more processing devices to modify the luminance values ~~color~~ ~~brightness~~ comprise instructions that, when executed, cause the one or more processing devices to adjust the pixel luminance, using a color look-up table.

38. (Currently Amended) The article of claim 32 ~~33~~ wherein the instructions that cause the one or more processing devices to modify the backlight intensity comprise instructions that, when executed, cause the one or more processing devices to modify a pulse width modulation signal that controls backlight illumination.

39. (Currently Amended) The article of claim 32 ~~33~~ wherein the instructions that cause the one or more processing devices to modify the backlight intensity further comprise instructions that, when executed, cause the one or more processing devices to:

determine a hardware register value corresponding to a baseline backlight intensity value;

apply a software generated value to the register value to generate a modified backlight intensity value; and

use the modified backlight intensity value to cause the backlight intensity to be modified.

40. (Original) The article of claim 39 wherein the baseline backlight intensity value is determined based on a user provided input.



41. (Original) The article of claim 39 wherein the baseline backlight intensity value is determined based on a power state of the display device.

42. (Currently Amended) An article comprising a computer-readable storage medium having stored thereon instructions that, when executed, cause one or more computing devices to:

determine an ambient light level for a display device having an adjustable backlight to provide variable backlight intensity;

modify the backlight intensity based on the ambient light level; and

modify ~~color~~ luminance values corresponding to or one or more portions of an image to be displayed on the display device based on the modified intensity of the adjustable backlight;

wherein modification to the luminance values approximately offsets the modification to the backlight intensity.

43. (Canceled)

44. (Original) The article of claim 42 wherein the instructions that cause the one or more processing devices to determine the ambient light level comprise instructions that, when executed, cause the one or more processing devices to receive a signal from an ambient light sensor indicating an ambient light level.

45. (Original) The article of claim 42 wherein the instructions that cause the one or more processing devices to determine the ambient light level comprise instructions that, when executed, cause the one or more processing devices to receive user input.

46. (Currently Amended) The article of claim 42 wherein the instructions that cause the one or more processing devices to modify the luminance values ~~color~~ ~~brightness~~ comprise instructions that, when executed, cause the one or more processing devices to adjust the pixel luminance, using a color look-up table.

47. (Original) The article of claim 42 wherein the instructions that cause the one or more processing devices to modify the backlight intensity comprise instructions that, when executed, cause the one or more processing devices to modify a pulse width modulation signal that controls backlight illumination.

48. (Previously Presented) The article of claim 42 wherein the instructions that cause the one or more processing devices to modify the backlight intensity comprise instructions that cause the one or more processing devices to:

determine a hardware register value corresponding to a baseline backlight intensity value;

apply a software generated value to the register value to generate a modified backlight intensity value; and

use the modified backlight intensity value to cause the backlight intensity to be modified.

49. (Original) The article of claim 48 wherein the baseline backlight intensity value is determined based on a user provided input.

50. (Original) The article of claim 48 wherein the baseline backlight intensity value is determined based on a power state of the display device.

51-60 (Canceled)